

KEWTECH

KT41

PRODUCT DATA SHEET

KT41

DIGITAL LOOP/ PSC TESTER

- 20, 200 & 2000Ω Loop measurement ranges
- PSC measurement up to 20kA
- Displays mains voltage before test
- Lock-down test button – for hands free testing
- Protected against phase to phase connection
- Instant correct wiring status check
- Complies with BS7671 (Part P)
- Does not require batteries



SPECIFICATIONS

LOOP TEST RANGES

Loop Impedance Ranges	0-20Ω, 0-200Ω, 0-2000Ω
Loop Impedance Accuracy	±(2% + 2dgt)
Lowest Resolution	0.01Ω

LOOP TESTING

AC Test Current	25A nominal
AC Test Period	20ms
PSC Ranges	0-200A, 0-2000A, 0-20kA
Operating Voltage	230V ± 10%, 50Hz
Insulation Resistance	50MΩ at 1000V ac between electrical circuit and housing case.
Withstand Voltage	3000V ac maximum for one minute between electrical circuit and housing case.

GENERAL

Fuse Protection	HRC Ceramic Fuses
Safety Standard	Designed to comply with the requirements of BS 4743
Dimensions	175 x 115 x 86mm
Weight	440g

ACCESSORIES

- KAMP 11 mains lead
- ACC016E 3 wire distribution board test leads
- ACCEP5 external earth probe
- Test lead pouch
- Carrying strap
- Instruction Manual
- Certificate of Conformity

OPTIONAL

- ACC016D 2 wire distribution board test leads
- Calibration Certificate